



Electrical:

| Specifications: | |
|--|---------------------------|
| Frequency Range: | 6.0 – 26.5 Ghz |
| Coupling: | 10.0 ± 1.00 dB |
| Insertion Loss: | 1.00 dB Max |
| Coupling Flatness: | ± 0.8 dB Max |
| Directivity: | 14 dB Typ |
| | 12 dB Min |
| VSWR: | 1.60:1 Max |
| Power Forward: | 25 Watts |
| Power Reflected: | 10 Watts |
| Power Peak: | 3 KW |
| Weight: | 0.8 / 22.7 Ounces / grams |
| Operating Temperature: | -40°C to +85°C |
| Input power is rated for load VSWR better than 1.20:1. | |
| Insertion loss does not include coupling loss. | |
| Coupling loss for 10 dB is 0.456 dB. | |

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SC1018118

Directional Coupler 10 dB 2.92mm Connectors

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.